

IPC-E3A4W-I40

4MP IR VF Eyeball Network Camera



قابلیت های کلیدی

- پشتیبانی از پروتکل ONVIF
- دمای کارکرد -30 تا +60 درجه سانتیگراد
- مقاومت در برابر نفوذ آب و گرد و غبار IP67
- Ultra265, H.265, H.264, MJPEG
- دارای میکروفون داخلی
- پشتیبانی از ROI
- OSD قابل تنظیم
- پشتیبانی از حالت راهرو 9:16
- IR هوشمند 40 تا 70 متر
- کاهنده نویز دیجیتال 3D

Specifications

Sensor	1/3", 4.0 megapixel, progressive scan, CMOS					Digital noise reduction	2D/3D DNR
Min. Illumination	Colour: 0.00 3 Lux (F1.6, AGC ON) 0Lux with IR					Smart IR	Supported
Day/Night	IR-cut filter with auto switch (ICR)					Flip	Normal/Vertical/Horizontal/180°/90°Clockwise/90°Anti-clockwise
Shutter	Auto/Manual, 1 ~ 1/100000s					Dewarping	N/A
Adjustment angle	Pan: 0° to 360°, Tilt: 0° to 75°, Rotate: 0° to 360°					HLC	Supported
S/N	>56dB					BLC	Supported
WDR	120dB					Defog	Digital Defog
Lens Type	2.8 ~ 12mm, AF automatic focusing and motorized zoom lens					Audio Compression	G.711
Lens Mount	Ø14					Suppression	Supported
Angle of View (H)	102.79°-30.86°					Sampling Rate	8KHZ
Angle of View (V)	54.50°-17.49°					Edge Storage	Micro SD, up to 256GB
Angle of View (D)	106.94°-35.49°					Network Storage	ANR, NAS(NFS)
DORI Distance	Lens (mm)	Detect (m)	Observe (m)	Recognize (m)	Identify (m)	Protocols	IPv4, IGMP, ICMP, ARP, TCP, UDP, DHCP, RTP, RTSP, RTCP, RTMP, DNS, DDNS, NTP, FTP, UPnP, HTTP, HTTPS, SMTP, SSL/TLS, QoS, 802.1x, SNMP)
	2.8	63.0	25.2	12.6	6.3	Compatible Integration	ONVIF (Profile S, Profile G, Profile T), API , SDK
	12	270.0	108.0	54.0	27.0	User/Host	Up to 32 users. 2 user levels: administrator and common user
IR Range	40-70m IR range					Security	Password protection, Strong password, HTTPS encryption, Export operation logs, Basic and digest authentication for RTSP, Digest authentication for HTTP, TLS 1.2, WSSE and digest authentication for ONVIF
Wavelength	850nm					Web Browser	Plug-in required live view: IE9+, Chrome 41 and below, Firefox 52 and below Plug-in free live view: Chrome 57.0+, Firefox 58.0+, Edge 16+, Safari 11+
IR On/Off Control	Auto/Manual					Network	10M/100M Base-TX Ethernet
Frame Rate	Main Stream: 4MP (2688*1520), Max 25fps; 4MP (2560*1440), Max 25fps; 3MP (2304*1296), Max 30fps; 1080P (1920*1080), Max 30fps; Sub Stream: 720P (1280*720), Max 30fps; D1 (720*576), Max 30fps; 640*360, Max 30fps; 2CIF(704*288), Max 30fps; CIF(352*288), Max 30fps; 128 Kbps-16 Mbps					Built-in Mic	Supported
Video Bit Rate	128 Kbps-16 Mbps					Power	DC 12V±25%, PoE (IEEE 802.3af) Power consumption: Max 8.0W
9:16 Corridor Mode	Supported					Dimensions (Ø x H)	Ø129 x 110mm (Ø5.1" x 4.3")
OSD	Up to 4 OSDs					Weight	0.67kg (1.48lb)
Privacy Mask	Up to 4 areas					Material	Metal
ROI	Up to 8 areas					Working Environment	-30°C ~ 60°C (-22°F ~ 140°F), Humidity: ≤95% RH (non-condensing)
Motion Detection	Up to 4 areas					Storage Environment	-30°C ~ 60°C (-22°F ~ 140°F), Humidity: ≤95% RH (non-condensing)
White Balance	Auto/Outdoor/Fine Tune/Sodium Lamp/Locked/Auto2					Storage Environment	6KV
Smart Features	Cross Line, Intrusion detection (based on human body detection), Audio detection					Reset Button	Supported
Image Setting	Image rotation, brightness, saturation, contrast, sharpness, gain adjustable by web browser					Ingress Protection	Ingression protection: IP67

Dimensions

